

Standard Series Waste Oil Drainers

| Description | Part No. |
|-------------|----------|
|-------------|----------|

Images and specifications can be subject to change without notice

Basic Type with Off-Set Drain Tube & Bowl (Not including Suction Probes)

76 litre capacity waste oil drainers.
All steel construction, powder coated grey finish.

Supplied with large capacity 20 litre drain bowl fitted with anti-splash filter and removable oversized funnel.

Units are emptied via low pressure air discharge (0.7 bar) through a 1.5 metre hose c/w hook end.

Heavy duty wheels and castors.
The clear sight gauge makes it easy to check oil level.
Handle is fitted with padded grip and tool tray beneath.

| | |
|---|-------------------|
| Basic gravity drainer c/w air discharge | GE24176 |
| As above but fitted with quick release male discharge Coupling | GE24176/QR |
| As above, but supplied with 3:1 wall mounted pump discharge kit | GE24276 |



Combination Waste Oil Drainers with Off-Set Drain Tube & Bowl (Inc. Suction Probes)

| | |
|--|----------------|
| Combination drainer without waste oil inspection chamber | GE25076 |
|--|----------------|

| | |
|--|----------------|
| Combination drainer fitted with waste oil inspection chamber | GE25576 |
|--|----------------|

| | |
|--|----------------|
| As GE25076 above, but fitted with a quick release male discharge Coupling. Supplied with 3:1 wall mounted pump discharge kit | GE25676 |
|--|----------------|



Mobile Oil Extractor (Inc. Suction Probes)

30 litre capacity mobile extraction unit. All steel heavy gauge construction, powder coated grey finish.

Unit is emptied via low pressure air discharge (0.7 bar) through a 1.5 meter hose c/w hook end.

Fitted with level sight gauge.

Handle is fitted with padded grip.

| | |
|---------------------------------|----------------|
| Oil extractor c/w air discharge | GE24230 |
|---------------------------------|----------------|



Accessories supplied as standard

The Extractor and combination oil drainers are supplied with a full set of probes and adaptors. Comprising of 5 x 700mm and 1 x 1000mm probes with adaptors to suit BMW, Mercedes, VW and Citroen.

They are fitted with a high performance low noise Vacuum Pump for dipstick extraction. Once depressurised the unit will work autonomously anywhere and does not require continuous connection to an air line.

Drainers supplied with a discharge pump kit include: a wall bracket, high flow 3:1 ratio pump, 1.5 metre suction discharge hose fitted with female 3/4" quick release coupling. 1.5 metre pump discharge hose for connection to waste oil pump system.

Note: The advantage of having a model fitted with an inspection chamber is that the user can check the condition and quantity of oil extracted.

