



Description	Specifications can be subject to change without notice	Part No.
LLD Open ABS Drum Hose Reels		
ABS Drum Spring Driven Double Arm Hose Reel		
For wall, ceiling and floor mounting. The Drum is made of high quality ABS with a high impact resistance. The Drum is mounted in a Carbon Steel Bracket covered in corrosion resistant powder coating. Double Arm Hose support with four guide rollers. When the hose is pulled out to the required length the operator can lock the hose in position on the hose reel's internal ratchet. This makes each operation safe and comfortable to use. Reels come with a 1000mm inlet hose the same diameter as the outlet hose.		
Open Hose Reel for Air, Water with 15m x 3/8" Hose with male 3/8" BSP Ends. SWP 20 bar (290psi).	GE83115	
Open Hose Reel for Oil with 10m x 1/2" Hose with male 1/2" BSP Ends. SWP 138 bar (2000psi).	GE82010	
Open Hose Reel for Oil with 15m x 1/2" Hose with male 1/2" BSP Ends. SWP 138 bar (2000psi).	GE82015	
Open Hose Reel for Grease with 10m x 1/4" Hose with male 1/4" BSP Ends. SWP 345 bar (5000psi).	GE84110	
Open Hose Reel for Hot High Pressure Water with 15m x 5/16" Hose with male 3/8" BSP Ends. SWP 200 bar (2900psi). All metallic parts made of 304 Stainless Steel. Max Temp: 100°C	GE86015	
Steel Swivel Bracket to suit the GE83115, GE82010, GE82015, GE84110 & GE86015 Retractable Hose Reels as above.	GE80000	
LLD Cased Hose Reels		
All Steel Cased Hose Reels for Air or Oil		
For wall, ceiling and floor mounting. The steel case has four guide rollers to protect the hose. When the hose is pulled out to the required length the operator can lock the hose in position on the hose reels internal ratchet. This makes each operation safe and comfortable to use. The reel comes with a 1000mm inlet hose the same diameter as the outlet hose.		
Cased Hose Reel for Oil with 9m x 1/2" Hose with male 1/2" BSP Ends. SWP 138 bar (2000psi).	GE82009	
Cased Hose Reel c/w Swivel Bracket for Oil with 15m x 1/2" Hose with male 1/2" BSP Ends. SWP 138 bar (2000psi).	GE82115	
LLD Heavy Duty Open Steel Hose Reels		
Heavy Duty Spring Driven Double Arm Hose Reel		
For wall, ceiling and floor mounting. The Drum is mounted in a Carbon Steel Bracket covered in corrosion resistant powder coating. Double Arm Hose support with four guide rollers. When the hose is pulled out to the required length the operator can lock the hose in position on the hose reels internal ratchet. This makes each operation safe and comfortable to use. Inlet hose not included but any length can be supplied with these reels.		
Open Hose Reel for Oil, Diesel, Air with 30m x 1/2" Hose with male 1/2" BSP Ends. SWP 138 bar (2000psi).	GE85030	
Open Hose Reel for Oil, Diesel, Air with 20m x 3/4" Hose with male 3/4" BSP Ends. SWP 87 bar (1260psi).	GE85020	
Open Hose Reel for Oil, Diesel, Air with 15m x 1" Hose with male 1" BSP Ends. SWP 69 bar (1000psi).	GE85015	